

# AC/DC<sup>®</sup> Transformers

[www.acdc.com.tr](http://www.acdc.com.tr)



## Isolation Transformers 3 Phase Input - 3 Phase Output



250 kVA

- Isolation Class : B,F or H
- Star, Delta, Zig-Zag and required angle of phase
- Laked Under Vacuum
- Dried in oven
- Construction Specification: Open type or protected type
- Plate or Ferrit Nuve
- 2 years warranty
- 10 years space part warranty

**TÜV**  
AUSTRIA  
HELLAS  
EN ISO 9001:2008

CE, ISO 9001

## Your Positive Energy source ...

MODEL	Tr3U-2503
The Feature of Transformer	Isolation Transformer
Type	Dry Type
Brand	AC/DC
Power	250 kVA
Isolation Class	Class B ( 120 °C ), Class F ( 155 °C ) or Class H ( 180 °C )
Place of Use	Indoor , Outdoor ( Optional )
With Box / Without Box	Without Box, With Box ( Optional )
Colling	Naturel Air ( AN ) or Forced Air ( AF )
Protection Class	IP20, IP23 ( Optional ), IP54 ( Optional )
Connections Group	YY, DY or another connect groups
Primer Voltage	400 VAC
Primer Frequency	50 / 60 Hz.
Primer Current	375 A
Seconder Voltage	400 VAC
Seconder Frequency	50 / 60 Hz.
Seconder Current	360 A
Endurance Voltage	3 kV RMS ( 1 Minute )
Connection	As per to customer requirements: All types of terminals and lugs
Colour	RAL 7032 ( Can be changed upon request )
Dimensions ( W x H x L ) (cm)	120 x 120 x 75
Weight ( kg )	900 kg.
Warranty	2 Year
<b>TRANSFORMER LIFETIME</b>	<b>10 YEARS</b>

\*\*\* AC/DC reserves the right to make any changes to data without prior notice.

Update: 06 / 08 / 2012

