

AC/DC[®] Transformers

www.acdc.com.tr



Isolation Transformers 3 Phase Input - 3 Phase Output



60 kVA

- Isolation Class : B,F or H
- Star, Delta, Zig-Zag and required angle of phase
- Laked Under Vacuum
- Dried in oven
- Construction Specification: Open type or protected type
- Plate or Ferrit Nuve
- 2 years warranty
- 10 years space part warranty

TÜV
AUSTRIA
HELLAS
EN ISO 9001:2008

CE, ISO 9001

Your Positive Energy source ...

| MODEL | Tr3U-0603 |
|-------------------------------|--|
| The Feature of Transformer | Isolation Transformer |
| Type | Dry Type |
| Brand | AC/DC |
| Power | 75 kVA |
| Isolation Class | Class B (120 °C), Class F (155 °C) or Class H (180 °C) |
| Place of Use | Indoor , Outdoor (Optional) |
| With Box / Without Box | Without Box, With Box (Optional) |
| Colling | Naturel Air (AN) or Forced Air (AF) |
| Protection Class | IP20, IP23 (Optional), IP54 (Optional) |
| Connections Group | YY, DY or another connect groups |
| Primer Voltage | 400 VAC |
| Primer Frequency | 50 / 60 Hz. |
| Primer Current | 90 A |
| Seconder Voltage | 400 VAC |
| Seconder Frequency | 50 / 60 Hz. |
| Seconder Current | 86 A |
| Endurance Voltage | 3 kV RMS (1 Minute) |
| Connection | As per to customer requirements: All types of terminals and lugs |
| Colour | RAL 7032 (Can be changed upon request) |
| Dimensions (W x H x L) (cm) | 85 x 90 x 70 |
| Weight (kg) | 370 kg. |
| Warranty | 2 Year |
| TRANSFORMER LIFETIME | 10 YEARS |

*** AC/DC reserves the right to make any changes to data without prior notice.

Update: 06 / 08 / 2012

